



Dry Erase

Specialty Screen Ink
CONVENTIONAL

Always test ink on substrate prior to production run. Please refer to the MSDS for safety precautions.

Description: When properly cured, Deco-Chem's Dry Erase ink becomes a rigid, transparent coating with outstanding chemical resistance. Use dry erase markers to mark the surface and wipe clean with a dry cloth without marring the surface.

Features:

- Excellent Flexibility
- Durability
- Easily Removable
- Chemical Resistant
- Excellent Gloss
- Abrasion Resistant

Substrates:

- Glass
- Mill Finish Aluminum
- Metal
- Epoxy Primed Aluminum
- Anodized Aluminum
- Stainless Steel

Stencil: Use a lacquer proof or direct emulsion film, photographic or water-soluble hand-cut stencil.

Coverage: 1,200-1,500 sq/ft. per gallon depending on ink deposit

Screen: 305 Mesh recommended for most applications.

Cure Parameters: Baking temperatures may vary depending on ink deposit, placement of parts in the oven and equipment. Pretests are recommended prior to production run.

250°F for 25 minutes
275°F for 15 minutes
300°F for 10 minutes
350°F for 8 minutes
400°F for 4 minutes
450°F for 3 minutes

Additives: 2032 Bubble Breaker, MBI94 Thinner and MBI95 Retarder

Cleaner: MBI96 Wash-Up

Storage: Ink should be stored in a metal container at room temperature (75°F). Inks previously used for printing runs should be stored in a separate container to avoid cross contamination. Ink has a minimum shelf life of 6 months from date of manufacture if the above guidelines are followed and there has been nothing added to the ink.

Sizes: 1 and 5 Gallon Pails or 30 or 55 Gallon Drums Available

Contact us today for a current product list and about customizing an ink's look, feel or texture just for you.

The information and recommendations contained in this product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on present knowledge and believed to be accurate. Information is based on technical data which the Seller believes to be reliable, and are intended for use by persons having skill and knowledge, at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice, or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent. Company policy of continuous product improvement may change the information contained in this product information sheet. Users are requested to ensure that they follow current recommendations.